



### TEHNICAL DATA:

- **Internal parts:** stainless steel
- **Fluid temperature:** -10°C to +90°C
- **Ambient temperature:** max +60°C
- **Viscosity:** max 21 mm<sup>2</sup>/s
- **Response time:** 5 - 120 ms
- **Voltage:** 230, 115, 48, 24 V AC / 24, 12 V DC
- **Duty cycle:** continuous (ED100%)
- **Electrical protection:** IP65  
(with plug to ISO 4400)  
Long term use in humid environment requires the use of sealing sets.

### 2/2 Closed when de-energised (NC)

Ports	Orifice size [mm]	Kv (water at 1 bar) [l/min]	Minimum ABSOLUTE pressure [mbar]	Body	Seal	Mass [kg]	Coil type	Model	Order code	Fig.
G3/8	7	13	15	Brass	NBR	0.52	TM35	D224	320717	1
G1/2	10	25	15	Brass	NBR	0.57	TM35	D240	340481	2
G1/2	12	40	15	Brass	NBR	0.43	TM30	M2451	301702	3
G3/4	18	65	15	Brass	NBR	0.76	TM35	M2521	301697	
G1	25	180	15	Brass	NBR	1.2	TM35	M2621	301699	
G6/4	40	330	15	Brass	NBR	2.75	TM40	M275	370810	4
G2	50	630	15	Brass	NBR	5.9	TM40	M282	391491	

### 3/2 Closed when de-energised (NC)

Ports	Orifice size [mm]	Kv [l/min] (water at 1 bar)	Minimum ABSOLUTE pressure [mbar]	Body	Seal	Mass [kg]	Coil type	Model	Order code	Fig.
G1/4	4.5	7.5	15	Brass	NBR	0.52	TM35	D32	330742	5

### OPTIONS:

- EEx me II explosionproof coils
- NPT ports
- Other versions on request.