



Ports	Orifice Size [mm]	Flow coefficient Kv [l/min] water at 1 bar	Differential pressure [bar]		Material		Mass [kg]	Coil type	Model	Voltage	Power [W]	Order code
			min	max	body	seal						
G1/4	1.8	1.5	0	10	Brass	NBR	0.35	TM30	D321	230 V AC	7	330511
										115 V AC	9	330560
										48 V AC	12	330520
										24 V AC	7	330530
										24 V DC	7	330540
										12 V DC	10	330550
										72 V DC	13	330502
NPT1/4	1.8	1.5	0	10	Brass	NBR	0.35	TM30	D321	230 V AC	10	330506
										115 V AC	9	330566
										24 V AC	7	330528
										24 V DC	7	330547
G1/4	1.8	1.5	0	10	Brass	EPDM	0.35	TM30	D321	230 V AC	7	334507
G1/4	1.8	1.5	0	10	INOX	FPM	0.35	TM30	D322N	200 V DC*	9	330517
									D321N	24 V AC*	7	330536
										24 V DC	10	330542
G1/4	1.8	1.5	0	25	Brass	NBR	0.52	TM35	D321	24 V DC	12	330740

\*Connected to 230VAC or 24VAC through plug with built-in rectifier (included).  
Low-noise design for applications that require very quiet operation.

